Venstar Non-Programmable Thermostat T2700



STANDARD FEATURES:

- Non-programmable
- 3 configurable outputs for maximum flexibility (MISC1, MISC2, MISC3)
- Accepts humidification/dehumidification control module (Venstar part number ACC0430)
- Auto changeover, 2-stage heat, 2-stage cool for use with gas/electric, heat pump, electric & hydronic heat
- Configurable for manual changeover
- Dry contact equipped
- Set point limiting
- Random Start
- Control to, or monitor a second remote sensor
- Display shows both heating an cooling setpoints and room temperature simultaneously
- All setpoints stored in non-volatile memory, and are never lost in power failure
- Service filter and service UV lamp indicators
- Red/Green LED shows whether thermostat is calling for heating or cooling
- 5-minute compressor time guard and adjustable cycle limit, both defeatable for servicing equipment
- Outdoor sensor ready (wired or wireless)
- Thermoglow backlit electro-luminous display and backlit color coded keys and legends
- Accepts accessory IR Remote Control system (Venstar part number ACC0431)
- Accepts accessory EZ Programmer (Venstar part number ACC0432)
- For accessory locking cover use (Venstar part number ACC0620)

MODEL:	T2700	QUANTITY:	DATE:
JOB NAME:			
LOCATION:			
BUYER:			BUYER P.O.#:
ENGINEER:			